

## TECHNICAL DATA SHEET

Date of issue: 2021

### ALPIDUR SOLVENTBASED PRIMER

#### DESCRIPTION

The solvent based primer ALPIDUR is transparent, micronized, waterproof, acrylic undercoat, with strong adhesion and high penetrance. It is highly recommended for priming surfaces painted with acrylic paints, emulsion paints, RELIEF, cement paint and sealants. It is suitable for the preparation of new surfaces and further strengthens and insulates porous surfaces, ensuring better adhesion for the paint. Waterproofs the surface while let it breathe.



#### TECHNICAL CHARACTERISTICS

<b>Density</b>	: 0,82 – 0,92 (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 25 – 35 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: 20 - 100% with solvent No803
<b>Coverage</b>	: 13 - 15 m <sup>2</sup> /lt per layer depends on the dilution and the surface absorption
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 2 – 3 hours
<b>Colors</b>	: Transparent
<b>Packaging</b>	: 750ml, 5lt, 20lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: “h”, Type:SB, Binding primers: 750g/l (2010). This product contains max 749g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No803 and then wash with hot water and soap.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Store at temperatures from 5°C to 40°C. Close the container after every use.



## TECHNICAL DATA SHEET

Date of issue: 2021

### APPLICATION

#### Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

<b>Dilution</b>	Walls: Up to 100% with solvent No 803 of <b>TETRALUX</b> . Terraces: Up to 20% with solvent No 803 of <b>TETRALUX</b> .
<b>Coverage</b>	Walls: Covers 13-15m <sup>2</sup> /lt per layer, depend on the dilution and the surface absorption Terraces: Covers 8-10m <sup>2</sup> /lt per layer, depend on the dilution and the surface absorption

### HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.