

TECHNICAL DATA SHEET

Date of issue: 2021

ALPINA CHASSISCOAT

DESCRIPTION

Special coating for sealing the lower part (chassis) of the car. Combination of antirust undercoat and final color based on alkyd resin. Its strong adhesion provides great resistance to washing, abrasion, engine oil and oil.



TECHNICAL CHARACTERISTICS

Density	: 1,10 – 1,18 (EAOT EN ISO 2811 20°C)
Viscosity	: 85-90KU
Thinning	: 5% with solvent No806
Coverage	: 12 - 14 m ² /lt per layer
Drying time	: Touch dry after 15 - 30 minutes and recoat able after 12hours
Colors	: Black, RAL shades
Packaging	: 750ml, 2.5lt, 5lt, 20lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category B: “e”, Type:SB, Special finishes: 840g/l (2010). This product contains max 839g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 and then wash with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.

APPLICATION



TECHNICAL DATA SHEET

Date of issue: 2021

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.