

TECHNICAL DATA SHEET

Date of issue: 2020

ALPISTONE SOLVENT BASED STONE VARNISH

DESCRIPTION

Transparent, acrylic, solvent based varnish of impregnation, specially designed for the protection and decoration of stone and artificial building materials. Provides long lasting protection and resistance at weather conditions. It has resistance at alkali surfaces and protects from atmospheric pollution. It has good adhesion, toughness and hit/scrub resistance. Quick drying and easy to apply. Ideal for concrete, natural stone, porous stones, bricks, tiles and every porous surface. Also, it is used for pavement yards, car sheds, loading platforms, tennis court, industrial and warehouse floors.



TECHNICAL CHARACTERISTICS

Density	: 0,80 – 0,83 (EAOT EN ISO 2811 20°C)
Viscosity	: 30 – 50 mPas (ASTM D2196-86 25°C)
Thinning	: Ready to use
Coverage	: 7 - 8 m ² /lt per layer depends on the dilution and the surface absorption
Drying time	: Touch dry after 1 hour
Colors	: Transparent
Packaging	: 750ml, 2.5lt, 5lt, 20lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “h”, Type:SB, Binding primers: 750g/l (2010). This product contains max 749g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No803 and then wash with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

The drying time depends on weather conditions. Do not paint on asphalt. Do not use on already painted surfaces or non-porous surfaces.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.