

## TECHNICAL DATA SHEET

Date of issue: 2020

# ALPIWOOD WATERBASED WOOD VARNISH

## DESCRIPTION

Water based odorless, acrylic varnish for interior and exterior use. It is applied to doors, windows, window frames and any wooden surface, highlighting the natural beauty of the wood and creating a wonderful gloss, satin or matte finish. It has excellent spreading and high resistance to adverse weather conditions without peeling or popping.



## TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,02 - 1,05 (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 2.000 - 3.000 mPas (ASTM D2196-86 25°C)
<b>Thinning</b>	: 5 – 10% with water for roller or brush, 10 – 20% for pistol
<b>Coverage</b>	: 9 – 12m <sup>2</sup> /lt per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 6 hours
<b>Packaging</b>	: 0.75lt, 2,5lt, 10lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: “e”, Type:WB, Interior/exterior trim varnishes and wood stains, including opaque wood stains: 130g/l (2010). This product contains max 129g/l VOC
<b>Painting tools</b>	: Brush, roller or pistol  Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.



## **TECHNICAL DATA SHEET**

**Date of issue: 2020**

---

### **APPLICATION**

#### **Stir well before use**

Surfaces must be clean, dry and free from foreign objects and substances and sanded with suitable sand paper.

### **HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.