

TECHNICAL DATA SHEET

Date of issue: 2020

BETOCONTACT ALPINA

DESCRIPTION

It is a specific resins improver of adhesion primer with quartz sand and high resistance to alkalis. It offers excellent adhesion on smooth surfaces such as architectural concrete, thermal insulation polystyrene plates, tiles etc.



TECHNICAL CHARACTERISTICS

Density	: 1,54 - 1,59 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 6.000 - 8.500 mPas (ASTM D2196-86 25°C)
Thinning	: Without dilution
Coverage	: 200 – 300g/m ²
Drying time	: Touch dry after 30 minutes and recoatable after 6-7 hours
Packaging	: 1kg, 5kg, 15kg
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “g”, Type:WB, primers: 30g/l (2010). This product contains max 29g/l VOC
Painting tools	: Brush, roller or appropriate pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.