

TECHNICAL DATA SHEET

Date of issue: 2020

EMULSION PAINT CASTEL ALPINA

DESCRIPTION

Emulsion paint for interior use, with high hiding power and coverage. It offers a bright, mat finish and a velvet surface. Suitable for professional use.



TECHNICAL CHARACTERISTICS

Density	: 1,60 - 1,64 (EΛOT EN ISO 2811 20°C)
Viscosity	: 107-116KU
Thinning	: 5 - 10% with water
Coverage	: 10-12 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of shades through tinting system of ALPINA.
Packaging	: White-Base P: 750ml, 3lt, 9lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25 @60°): 30g/l (2010). This product contains max 29g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

New surfaces	1^o layer: Priming with acrylic water based primer or water based primer ALPIDUR 2^o layer: One layer of Emulsion paint Castel. Dilution 5-10% with water 3^o layer: One layer of Emulsion paint Castel. Dilution 5-10% with water
Painted surfaces	Scratch, fill and prime with acrylic water based primer or water based primer ALPIDUR if it's necessary and apply two layers of Emulsion paint Castel diluted 5-10% with water

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.