

## TECHNICAL DATA SHEET

Date of issue:2020

### EMULSION PAINT EXTRA ALPINA

#### DESCRIPTION

Emulsion paint of excellent quality for interior and exterior use. It has great hiding power, high spreading rate and it gives a luxurious, matt finish. There is unlimited number of shades.



#### TECHNICAL CHARACTERISTICS

|  |  |
|--|--|
| <b>Density</b>                         | : 1,35 - 1,52 depending on the shade(EAOTENISO 2811 20°C)  |
| <b>Viscosity</b>                       | : 99 - 105 Ku (ASTM D562)  |
| <b>Resistance to wet abrasion</b>      | : >5.000cycles(DIN 53778)  |
| <b>Thinning</b>                        | : 5-10% with water   |
| <b>Coverage</b>                        | : 12m <sup>2</sup> /lt per layer   |
| <b>Drying time</b>                     | : Touch dry after 1 hourand recoat able after 2-3hours   |
| <b>Colors</b>                          | : Unlimited number of shades through tinting system of ALPINA.   |
| <b>Packaging</b>                       | : White-Bases: 750ml, 3lt, 10lt  |
| <b>VOC (VolatileOrganic Compounds)</b> | : EU limit value for this product Category A: “a”, Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 29g/l VOC. |
| <b>Painting tools</b>                  | : Brush, roller, pistol<br><br>Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.            |
| <b>Conditions of application</b>       | : Do not apply at temperatures below 10°Cand above 35°C.   |
| <b>Storage</b>                         | : Store at temperatures from 5°C to 40°C. Close the container after every use.   |



## TECHNICAL DATA SHEET

Date of issue:2020

### APPLICATION

#### Stirwellbeforeuse

Surfaces must be clean, dry and free from foreign objects and substances

|                         |  |
|-------------------------|--|
| <b>New surfaces</b>     | <b>1°layer:</b> Priming with solventbased or waterbased primer ALPIDUR<br><b>2°layer:</b> One layer of Emulsion paint Extra. Dilution 5-10% with water<br><b>3°layer:</b> One layer of Emulsion paint Extra. Dilution up to 10% with water |
| <b>Painted surfaces</b> | Scratch, fill and prime with primer ALPIDUR if it's necessary and apply two layers of Emulsion paint Extra diluted 5-10% with water  |

### HEALTH, SAFETYAND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.