

TECHNICAL DATA SHEET

Date of issue: 2020

EMULSION PAINT SUPER ALPINA

DESCRIPTION

Emulsion paint for interior use. It's economical, providing great hiding power and spreading rate. It is suitable for professional use. Unlimited number of shades through tinting ColourSystem of Alpina.



TECHNICAL CHARACTERISTICS

Density	: 1,57 - 1,62 depending on the shade (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 105 - 115 KU (ASTM D2196-86 25°C)
Resistance to wet abrasion	: >1.000 cycles(DIN 53778)
Thinning	: 5 - 10% with water
Coverage	: 12 m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of shades through tinting system of ALPINA.
Packaging	: White-Bases: 750ml, 3lt, 9lt
VOC (Volatile Organic	: EU limit value for this product Category A: "a", Type:WB, Interior matt
Compounds)	walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 29g/l VOC.
Painting tools	: Brush, roller, pistol
	Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances		
New surfaces	1°layer: Priming with solvent based or water based primer ALPIDUR	
	2º layer: One layer of Emulsion paint Super. Dilution 5% with water	
	3º layer: One layer of Emulsion paint Super. Dilution up to 5% with water	
Painted surfaces	Scratch, fill and prime with primer ALPIDUR if it's necessary and apply two layers of Emulsion paint Super diluted 5-10% with water	

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.