

TECHNICAL DATA SHEET

Date of issue: 2020

EMULSION WATERBASED PRIMER ALPINA

DESCRIPTION

It is a whitish water based undercoat for emulsion paints of internal use. Creates better adhesion conditions and stabilizes the surface. It shows great performance and an economical way priming interior walls.



TECHNICAL CHARACTERISTICS

Density	: 1,29 - 1,32 (ΕΛΟΤ EN ISO 2811 20°C)
Viscosity	: 6.500 - 7.500 mPas (ASTM D2196-86 25°C)
Thinning	: Dilute with water at a ratio of 1 part primer 4 parts water
Coverage	: 25 – 30m ² /lt per layer
Drying time	: Touch dry after 1 hour
Packaging	: 0.75lt, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “g”, Type:WB, primers: 30g/l (2010). This product contains max 29g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.