

TECHNICAL DATA SHEET

Date of issue: 2020

HYDROCHROMA ALPINA

DESCRIPTION

Hydrochroma of ALPINA is an acrylic base paint of exceptional quality and durability for interior use. It offers excellent coverage, especially suitable for ceilings, but also for walls of basements, bathrooms, etc., allowing the surfaces to breathe and not to turn yellow, giving them a matte, white colour.



TECHNICAL CHARACTERISTICS

Density	: 1,67 - 1,70 (EAOT EN ISO 2811 20°C)
Viscosity	: 9.500 - 11.500 mPas (ASTM D2196-86 25°C)
Thinning	: 15 – 30% with water
Coverage	: 9 – 12m ² /l per layer
Drying time	: Touch dry after 1 hour and it's recoatable after 2-3hours
Colors	: Light shades through tinting system of ALPINA.
Packaging	: 0.75lt, 3lt, 9lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: "a", Type:WB, Interior matt walls and ceilings (Gloss <25@60°): 30g/l (2010). This product contains max 29g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.
It is diluted 30% with water for white and 15% for the shades.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.