

## TECHNICAL DATA SHEET

Date of issue: 2020

# VELATOURA WATERBASED ALPINA

## DESCRIPTION

Water based substrate of premium quality, suitable for interior and exterior wooden surfaces. It offers excellent adhesion to new and previously painted surfaces. It spreads uniformly, ensuring excellent adhesion in the final color. It is odorless and friendly to the environment and the user. Ideal for undercoat for waterbased enamel paints.



## TECHNICAL CHARACTERISTICS

<b>Density</b>	: 1,25 - 1,26 (EAOT EN ISO 2811 20°C)
<b>Viscosity</b>	: 2.500 - 3.500 mPas (ASTM D2196-86 25°C)
<b>Resistance to wet abrasion</b>	: 10.000 cycles(DIN 53778)
<b>Thinning</b>	: 5 with water for roller or brush, 10 – 20% for pistol
<b>Coverage</b>	: 10 m <sup>2</sup> /lt per layer
<b>Drying time</b>	: Touch dry after 1 hour and recoat able after 5-6hours
<b>Colors</b>	: Unlimited number of shades through tinting system of ALPINA.
<b>Packaging</b>	: 750ml, 2.5lt, 10lt
<b>VOC (Volatile Organic Compounds)</b>	: EU limit value for this product Category A: “d”, Type:WB, Interior/exterior trim and cladding paints for wood and metal: 130g/l (2010). This product contains max 129g/l VOC.
<b>Painting tools</b>	: Brush, roller, pistol  Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
<b>Conditions of application</b>	: Do not apply at temperatures below 10°C and above 35°C.
<b>Storage</b>	: Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.



---

## **TECHNICAL DATA SHEET**

**Date of issue: 2020**

---

### **APPLICATION**

---

#### **Stir well before use**

---

Surfaces must be clean, dry and free from foreign objects and substances.  
It is applied in two layers for a perfect result. It dries in one hour and it can be recoated after 5-6 hours.  
These times depend on weather conditions.

---

### **HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION**

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.