

TECHNICAL DATA SHEET

Date of issue: 2020

SOLVENT BASED VELATURA ALPINA

DESCRIPTION

A high quality, alkyd undercoat suitable for interior and exterior wooden and putty surfaces. It has great whiteness and hiding power, it can be rubbed and applied easily, without affect the final gloss of the enamels.



TECHNICAL CHARACTERISTICS

Density	: 1,49 – 1,52 (EAOT EN ISO 2811 20°C)
Viscosity	: 80-85KU (25°C)
Thinning	: 5% with solvent No803
Coverage	: 13 - 14 m ² /lt per layer
Drying time	: Touch dry after 3 hours and recoat able after 16 hours
Colors	: Unlimited number of shades through tinting system of ALPINA.
Packaging	: 750ml, 2.5lt, 20lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “g”, Type:SB, Primers: 350g/l (2010). This product contains max 349g/l VOC.
Painting tools	: Brush, roller, pistol Remove as much paint as possible from the equipment in the container and clean it immediately with solvent No806 or No803 and then wash with hot water and soap.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Store at temperatures from 5°C to 40°C. Close the container after every use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances.

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.