

TECHNICAL DATA SHEET

Date of issue: 2020

ALPIDUR ΑΣΤΑΠΙ ΝΕΡΟΥ

DESCRIPTION

Transparent, micronized, waterproof undercoat with strong adhesion for the insulation of vertical and horizontal surfaces. It is suitable for plastic, acrylic and insulating paints. It is odorless. Ideal for absorbent surfaces, such as plaster, putty surfaces, etc.



TECHNICAL CHARACTERISTICS

Density	: 1,00 (EAOT EN ISO 2811 20°C)
Viscosity	: 5 mPas (ASTM D2196-86 25°C)
Thinning	: 50 – 100% with water
Coverage	: 15 - 20m ² /lt per layer
Drying time	: Touch dry after 1 hour and recoat able after 2-3hours
Colors	: Unlimited number of light shades through tinting system of ALPINA.
Packaging	: 750ml, 3lt, 10lt
VOC (Volatile Organic Compounds)	: EU limit value for this product Category A: “h”, Type:WB, Binding primers: 30g/l (2010). This product contains max 14g/l VOC
Painting tools	: Brush, roller or pistol Remove as much paint as possible from the equipment and clean it immediately with hot water and soap. Do not dispose liquids of cleaning equipment into environment.
Conditions of application	: Do not apply at temperatures below 10°C and above 35°C.
Storage	: Keep in shadow in temperature 5°C to 40°C. Keep container closed after each use.



TECHNICAL DATA SHEET

Date of issue: 2020

APPLICATION

Stir well before use

Surfaces must be clean, dry and free from foreign objects and substances

HEALTH, SAFETY AND ENVIRONMENTAL INFORMATION

Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult ALPINA Safety Data Sheets and follow all local or national safety regulations.